

96

MT-100 SIP Phone With Camera

All in One / PSDN / 10.1-inch Full touch Screen / 1080P



Product Features

All-in-One Integration Design

Integrated HD camera, microphone, speaker, highperformance video codec, single device connected to the network and connect with display device to hold meeting.

10.1-inch Full touch Screen

10.1 inches high-definition display, full touch operation and humanized UI interaction interface, No matter video conference or conference call operation can be easily started.

Built-in Android

Built-in Android operating system, support a variety of thirdparty software to achieve more function expansion.

1080P Camera

Built-in 1080P Camera, support 1080P Video Conference.

External Large Screen

The external display screen can display local or remote video on the same screen to obtain a better conference experience.

Support HDMI or wireless Video in

A PC can be connected through HDMI-in or the wireless projection mode, and the PC screen can be accessed as an auxiliary stream, To meet the needs of accessing auxiliary streams in various ways in a conference scenario,Video conferencing is more efficient.

Compatible with PSTN and sip protocols

Compatible with PSTN and SIP network telephone access. without mutual influence.

Open SDK Interface

Built-in Android operating system, fully open SDK interface, can meet the needs of different industries Summation and custom capability.

Screen Angle Adjustable

The integrated damping handle bracket can adjust the screen angle at any time.





Hardware Platform

Video Features

1080PUSB Camera

Touch Screen

Operating System	Android 9.0	
CPU	4-core A73+2-core A53 (4-core A55 optional), can reach to 1080P@30fps even with CPU soft coding;	
Super NPU	5TOPS	
Memory	2GRAM+8GBROM	
Video Codec Coding	H.264/H.265, 1x1080P@60fps,2X1080P@30fps Decoding: VP9Profile-2, 4Kx2K@60fps (max.); H.265HEVCMP-10@L5.1, 4Kx2K@60fps (max.); AVS2-P2Profile, 4Kx2K@60fps (max.); H.264AVCHP@L5.1, 4Kx2K@30fps (max.); H.264MVC, ;1080P@60fps (max.)	
WIFI Standard	IEEE802.11a/b/g/n/ac, WPA, WPA2	
Bluetooth	BT 5.0	

Interfaces

USB Interface	2 x USB 2.0Type-C(host)
HDMI Interface	1 x HDMI IN; 1 x HDMI OUT
Network Interface	2 x RJ45:10M/100M/1000M Base-T 1 x WiFi
Handset Interface	1 x RJ9
Phone Interface	1 x RJ11
Power Interface	1 x DC12V

General Specifications

es	Dimension	243mm x 164mm x 33mm
	Speaker	1 x 3W
10.1-inch IPS touch screen supporting 10-point touch control Resolution: 1280x800 Visual angle: 170 degrees	Microphone	2 x mic Pickup 6M
	Environmental Requirements	• Operating Temperature: 0° C to
Sensor: 1/2.8 inches CMOS, Effective Pixel: 207MP Scanning Mode:Progressive Focal length: f=2.8mm, Horizontal FOV: 90° Minimum Illumination: 0.5Lux@(F1.8,AGCON) Shutter: 1/30s~1/10000s UVC1.1		40°C • Operating Humidity: 10% to 80% • Non-Operating Temperature: -40° to -70°C • Non-Operating Humidity (non- condensing): 0% to 95% • Ambient Noise: < 46dBA SPL
	Certification and Standards	CCCRoHS